

**SLITTER REWINDER**  
**COMPACT DUPLEX TURRET TYPE**



# Slitter Rewinder

## Compact Duplex Turret Type

Excellent performance compact machine. Easy to operate. **Specially designed for converters who need high production and time optimization.**

This machine operates with: cellophane, PET, PE, PVC, BOPP, BOPA, laminations, CPP and label.

### PROCESS

- Shaftless non-pivotable unwinder of 3" and 6" (optional).
- Alignment system by register line.
- Shear-cut system.
- Turret type system with 4 differential shafts of 3".
- Cross cutting system.

### TECHNICAL SPECIFICATIONS

- Unwind diameter: 1,000 mm (39").
- Rewind diameter: 600 mm (23").
- Standard widths: 1,000 mm (39") – 1,300 mm (51") – 1,600 mm (62").
- Minimum slitting width: 38 mm (1.5").
- Speed: 500 m/min (1,640 ft/min) or 750 m/min (2,460 ft/min).

### OPTIONALS

- Shear slitting system.
- Manual or semi-automatic core positioning laser system.
- Rewind roll unloader.
- Turret winding shafts support.
- Differential shafts in different diameters.
- Lifting table system at unwinder to load the roll (patented system).
- Remote connection for fast troubleshooting.

### SERVICES

- After-sales service.
- Technical support.
- Spare parts sales.